



Secure USB Drive Customization Program

Now you can customize Kingston's secure USB Flash drives in a variety of ways to meet your organization's needs. Add selected features to create unique, indispensable drives.

Kingston® offers easy and convenient ordering for your customized secure USB drive through your preferred reseller.

Kingston's line of secure USB products includes the DTVP, DTVP-M, DT4000, DT4000-M, DT5000, DT6000

Please note: minimum orders are 50 pieces; contact your reseller for details.

Select any or all of the following customization options!:

○ Serial Numbering



We have several options for serialization to suit your asset tracking needs. The metal casing of the drive can be laser-etched with a serial number that uniquely identifies each drive. This external laser etched serial number can be matched to the unique internal, USB device serial number as well.

Device Serialization Options:

- Add a 24 character, 2D bar-coded serial number with matching USB device serial number. Perfect for asset tracking and remote identification of all USB drives. Useful for white listing with endpoint management software.

- Serial numbers and format assigned by Kingston only⁴
 - Provide a list of all USB serial numbers in Excel format when product order is shipped.

- Customer defined sequential serial number range etched on outer casing only.

- Specify the number of characters and format, and numerical range (24 characters maximum):

- _____
- Include 2D bar-code of serial number (up to 24 characters)
 - Include 1D bar-code of serial number (18 characters maximum)

- Other. Please specify requirements:

[more >>](#)

○ Custom Product Identification (PID)

Each Kingston secure USB drive can be uniquely identified by the combination of the Kingston USB Vendor ID (VID), the product line USB PID, and the device USB serial number. Kingston can also assign a custom PID that is unique to your organization. This custom PID allows you to white list this PID with standard end-point management software so that only the Kingston Secure USB drives purchased for your organization will function at the endpoints. Kingston's USB VID is 0951. Customer should provide alphanumeric PID, 4 characters, 0-9, A-F.

○ Capacities

Kingston can set the capacity of the secure USB drive to any data restrictions you may have, for example, 1GB, 512GB, 96MB

○ Custom Content Load

Kingston can load digital files directly onto the CD partition of the drive. The CD partition is read-only, to protect your organization's important files from accidental deletion.

Please supply:

- A Checksum² and screenshot of file/folder layout
 - An email address for the customer to issue 1) a secure Kingston FTP link for content transfer and 2) a legal agreement regarding the rights of the content and accept all legal responsibility for the content³
-

○ Custom Logo/Marking Laser Etching

Laser-etch your drive to create a unique look or present vital information.

Please supply:

- Adobe Illustrator Vector-Based .eps or .ai file of your artwork (27.5mm x 6.5mm)
 - An email address for the customer to issue a legal agreement regarding the rights of the artwork/logo and accept all legal responsibility for the artwork/logo
-



○ Custom Color (Green, Red or Gray)

Kingston's customization program offers Green, Red or Gray color casing options to help class identification at government agencies and other needs.

Color choice:

- Green
- Red
- Gray

○ Profile Customization

The custom profile options let you create a fully unique product. Your specific security requirements can be addressed through custom profile changes listed below. Changing the profile allows you to create a drive with personal settings and options.



Feature	Default Setting	Custom Option
<input type="checkbox"/> Custom USB Product Name Indicates the USB product name	DTVP, DT4000, DT5000, DT6000	Max. 16 characters
<input type="checkbox"/> Number of password attempts The drive locks down and will need reformatting after a certain number of attempts	10	Between 3 and 25 attempts
<input type="checkbox"/> Support URL Address Each drive contains a support webpage	kingston.com/support	Customer defines the URL address
<input type="checkbox"/> CD Partition Drive Label Drive includes a CD-ROM partition that is labeled	DTVP, DT4000, DT5000, DT6000	Max. 11 characters Must be different than Removable Drive Label
<input type="checkbox"/> Removable Drive Label The name of the drive on the computer	KINGSTON	Max. 11 characters Must be different than CD Label
<input type="checkbox"/> Minimum Password Length Specifies the minimum password length	6 ⁵	Max. 128 (DT5000, DT6000) 16 (DTVP, DT4000) characters
<input type="checkbox"/> Password Similarity Checking Various password hint options	Exact	None, Exact, or Similar
<input type="checkbox"/> Password Hint The user can enter text as reminder of password	Enable	Disable (no password hint)
<input type="checkbox"/> Remaining Password Attempt Warning Number of attempts left prior to drive lock-down	3	Between 1 and the Maximum Password Attempts
<input type="checkbox"/> User Settable Contact Name Determines whether or not a user can set/edit the Contact Name	Enable	Disable (user cannot change Contact Name)
<input type="checkbox"/> Preset Contact Name The contact name as it appears on the drive	none	Max. 32 characters
<input type="checkbox"/> User Settable Company Determines whether or not a user can set/edit the company	Enable	Disable (user cannot change the Company)
<input type="checkbox"/> Preset Company The name of the company as it appears on the drive	none	Max. 32 characters
<input type="checkbox"/> User Settable Detail Determines whether or not a user can set/edit detail	Enable	Disable (user cannot change the detail)
<input type="checkbox"/> Preset Detail The detail as it appears on the drive	none	Max. 156 characters, up to 4 lines of text

¹ Additional fees will apply. Some options may not be available on all encrypted DataTravelers. Contact your reseller for details.

² Checksum is a form of redundancy check; a simple way to protect the integrity of data by detecting errors in transmitted data.

³ Kingston is not responsible for third-party content. Testing and technical support must be provided by any third-party software company.

⁴ DT5000 and DT6000 — 16 Character, 2D or 1D barcode, unique Serial Number, Non-Sequential

⁵ DT4000 has a minimum password length of 8 characters

©2011 Kingston Technology Corporation, 17600 Newhope Street, Fountain Valley, CA 92708 USA.

All rights reserved. All trademarks and registered trademarks are the property of their respective owners. Printed in the USA MKF-217.4

